



reddot award 2017
winner



shot

Design: Sebastian David Büscher


Lichttechnik:
230V Power LED
IvyLight-technology
3000K warmweiß
L70/50.000 h
Flood Reflektor symmetrisch
dimmbar
Anschluss:
5 m Zuleitung inkl.
Schutzkontaktstecker
anschlussfertig

Material:
Aluminiumguss
ESG Glas klar
Schutzart:
IP65
EEK:
A+

light technology:
230V Power LED
IvyLight-technology
3000K warm white
L70/50.000 h
flood reflector symmetric
dimmbable
connection:
5 m supply cable
incl. safety plug
ready to connect

material:
aluminium die-casting
tempered safety glass clear
protection class:
IP65
EEC:
A+

shot 4 W



Größe in mm
size in mm

Art.-Nr.
item no.

Farbe
colour

Leistung
power

Lichttrichtung
light direction

91090-4W-AN

anthracite
RAL 7016

4 W/350 lm




91090-4W-CB

cool brown

4 W/350 lm



shot 15 W



Größe in mm
size in mm

91090-15W-AN

anthracite
RAL 7016

15 W/1350 lm



91090-15W-CB

cool brown

15 W/1350 lm



+ Anschluss optional mit IP44.de connect.
connection with IP44.de connect as an option.


IP44.de outside lighting

Marienstraße 13 . 33378 Rheda-Wiedenbrück . Germany
T +49 5242 5797-0 . F +49 5242 5797-10
welcome@IP44.de . www.IP44.de

IP44.de behält sich spätere Produktanpassungen auch ohne Ankündigung vor.
IP44.de reserves the right to product adaptations at any time, without prior notice.



tee shot



Größe in mm
size in mm

Art.-Nr. item no.	Artikel article	Material material
91091-AN	 anthracite RAL 7016	Schale: Aluminiumguss Stab: Edelstahl beschichtet bowl: aluminium die-casting pole: stainless steel coated
91091-CB	 cool brown	Schale: Aluminiumguss Stab: Edelstahl beschichtet bowl: aluminium die-casting pole: stainless steel coated