



como down Design: IP44.de

Lichttechnik:
230V Power LED
IvyLight-technology
3000K warmweiß
L70/50.000 h

dimmbar

Installation:
1 x Kabeleinführung;
Anschlussklemme
3 x 1,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Glaslinse

Schutzart:
IP65

EEK:
A+

light technology:
230V Power LED
IvyLight-technology
3000K warm white
L70/50.000 h


dimmbare

installation:
1 x cable entry point;
connection terminal
3 x 1,5 mm²

material:
aluminium die-casting
powder-coated
glass lens

protection class:
IP65

EEC:
A+



Größe in mm
size in mm

Art.-Nr. item no.	Farbe colour	Systemleistung system performance	Lichtrichtung light direction
92180-D-AN	anthracite RAL 7016	6 W/300 lm	
92180-D-CB	cool brown	6 W/300 lm	
92180-D-SG	space grey	6 W/300 lm	
92180-D-WH	pure white RAL 9016	6 W/300 lm	
92180-D-BL	deep black RAL 9005	6 W/300 lm	

IP44.de outside lighting
Mühlenstraße 20 . 33378 Rheda-Wiedenbrück . Germany
T +49 5242 5797-0 . F +49 5242 5797-10
welcome@IP44.de . www.IP44.de

IP44.de behält sich spätere Produktanpassungen auch ohne Ankündigung vor.
IP44.de reserves the right to product adaptations at any time, without prior notice.