



slat Design: Klaus Nolting

Lichttechnik:
230V Power LED
IvyLight-technology
3000K warmweiß
L70/50.000 h

dimmbar

Installation:
2 x Kabeleinführung;
Anschlussklemme
3 x 1,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Sicherheitsglas satiniert

Schutzart:
IP65

EEK:
A

light technology:
230V Power LED
IvyLight-technology
3000K warm white
L70/50.000 h


dimmbare

installation:
2 x cable entry point;
connection terminal
3 x 1,5 mm²

material:
aluminium die-casting
powder-coated
safety glass satined

protection class:
IP65

EEC:
A



Größe in mm
size in mm

Art.-Nr. item no.	Farbe colour	Systemleistung system performance	Lichttrichtung light direction
91130-AN	anthracite RAL 7016	16 W/360 lm	
91130-CB	cool brown	16 W/360 lm	
91130-SG	space grey	16 W/360 lm	
91130-WH	pure white RAL 9016	16 W/360 lm	
91130-BL	deep black RAL 9005	16 W/360 lm	

IP44.de outside lighting

Mühlenstraße 20 · 33378 Rheda-Wiedenbrück · Germany
T +49 5242 5797-0 · F +49 5242 5797-10
welcome@IP44.de · www.IP44.de

IP44.de behält sich spätere Produktanpassungen auch ohne Ankündigung vor.
IP44.de reserves the right to product adaptations at any time, without prior notice.